




ACETYLENE

TRANSPORT INFORMATION: UN No. 1001	 UNITED STATES OF AMERICA	 CANADA	 MEXICO
Shipping Name:	Acetylene, Dissolved	Acetylene	Acetylene, Dissolved
Hazard Class:	2.1	2.1	2.1
Label:	Flammable Gas	Flammable Gas	Flammable Gas

FORMULA: C_2H_2
 MSDS REFERENCE: 4559
 CAS No.: 74 - 86 - 2
 GENERAL DESCRIPTION:
 Colorless, highly flammable gas.

Product and Package Information

PART NO.	PRODUCT GRADE	QUALITY ASSAY/SPECIFICATION	CYLINDER STYLE	CONTENT ft^3 / m^3	REGULATOR RECOMMENDATIONS
					SEE REFERENCE GUIDE (SECTION F, PAGE 2)
AC 2.6AA	2.6 ATOMIC ABSORPTION*	99.6 % $O_2 + CH_4 < 4000$ ppm $PH_3 < 20$ ppm	A8	360 / 10.19	202 SERIES

*Specially purified and prepared for use in all atomic absorption spectrophotometers.

CAUTION: Do not discharge acetylene at pressures exceeding 15 psig/104 kPa, gauge, therefore use Regulator 202-5651.

Cylinder style availability varies by location.

For ordering purposes, please add the desired cylinder style to the end of the above part number.

SEE SECTIONS G AND H FOR SAFETY AND TECHNICAL INFORMATION.

Cylinder Information

CYLINDER STYLE / CGA	PRESSURE psig / kPa, gauge	GROSS WEIGHT lb / kg
A8 / 510	250 / 1724	207 / 94

Praxair, your full line supplier for specialty gases and equipment.

